

CONTROLLERS

RGB\RGBW\CCT APP /HANDSET/WALL/WIFI/RJ45

RGBW-MAX



5in1 WIFI Sync Controller Multi Syncs RGBW/RGB/CCT/RGBCCT 15A-4 Zones . Suitable for: LST30RGB / COB840RGBW

Specification:

- Working voltage: DC12/24V
- Max Load Current: 15A, 6 Channel
- DC12V: 180W , DC24V: 360W
- App: Smart Life (Multi Sync) or Tuya (individual)
- Group Sync Controller (Max of 4)
- External Dimension: 122x38x22mm
- 2 Year Warranty

Tuya App / Smart Life App (for Multi Syncs)

WIFI + Handset Infra red RGBW & RGB Controller 6Amp

Suitable for: LST30RGB / COB840RGBW



RGBW-MINI

Specification:

- Working voltage: DC12/24V
- Max Load Current: 6A, 5 Channel
- DC12V: 72W , DC24V: 144W
- App: Smart Life (Multi Sync) or Tuya (individual)
- 2 Year Warranty



RJ45-RGBW

Radio Frequency Touch Controller Multi Syncs 12V/24 32Amp RJ45 Receiver.

Master Unit . Multi Syncs


Suitable for: LST30RGB / COB840RGBW



Specification:

- Working voltage: DC12/24V
- Max Load Current: 32A
- DC12V: 384W , DC24V: 768W
- Sync with other controllers using Ethernet RJ45 cable
- External Dimension: 91x91x24mm
- 2 Year Warranty



(not included)



 <p>RJ45WL-RGBW</p>  <p>(not included)</p>	<p>Wall Radio Frequency Touch Controller Multi Syncs 12V/24 32Amp RJ45 Receiver. Standard Size Patress . Master Unit Multi Syncs</p> <p>Suitable for: LST30RGB / COB840RGBW</p> <p>Specification:</p> <ul style="list-style-type: none"> • Working voltage: DC12/24V • Max Load Current: 32A • DC12V: 384W , DC24V: 768W • Sync with other controllers using Ethernet RJ45 cable • External Dimension: 91x91x24mm (Fits Std. Single Backboxes) • 2 Year Warranty  
<p>RJ45x-RGBW</p> 	<p>Extra/Additional/ Secondary Controllers Multi Syncs 12V/24 32Amp RJ45 Receiver units.</p> <p>Suitable for: LST30RGB / COB840RGBW</p> <p>Specification:</p> <ul style="list-style-type: none"> • Working voltage: DC12/24V • Max Load Current: 32A • DC12V: 384W , DC24V: 768W • Sync with other controllers using Ethernet RJ45 cable • External Dimension: 91x91x24mm • 2 Year Warranty 
<p>LST-PROTLS</p> 	<p>Inner Profiles Touchless Wave Dimmer Switch PWM 12/24V 3/5Amp</p> <p>Suitable for: LST60 / LST66 / KIT60 / COB420 / CPR420</p> <p>Specification:</p> <ul style="list-style-type: none"> • Working voltage: DC12/24V • Max Load Current: 3A for 12V (36W) / 5Amp for 24V (120W) • External Dimension: 50x10x3mm • 2 Year Warranty
 <p>AMP12</p>	<p>Amplifier for RGB Strip 12V/24V</p> <p>Ideal for LED RGB Strips parallel wiring configuration using 1 controller only</p> <p>Suitable for: LST30RGB</p> <ul style="list-style-type: none"> • Operating voltage: DC12/24V • Max Load Current: 4A for each colour • DC12V: 144W , DC24V: 288W • External Dimension: 105x65x25mm • 2 Year Warranty